

SVAN 954 ORDERING INFORMATION

Below you will find the informations about SVAN 954 instrument configuration and related parts available in SVANTEK offer.

All parts and options not included in a basic version of SVAN 954 set are subjects to be priced additionally.

With any questions about prices etc. please contact local representative or send an email to info@acu-vib.com.au



The basic version of SVAN 954 set consists of:

SVAN 954	Vibration Meter
SV 3185D	Single axis general purpose accelerometer 100 mV/g
SC 27	Coil cable (TNC plug to TNC plug), providing connection of the SV 3185D accelerometer with the SVAN 954 instrument
SC 56	USB cable for communication with the PC
SvanPC+	Base module software for data download, visualisation and easy export to other applications
Certificate	Manufactory calibration certificate
Batteries	Four AA alkaline batteries

SVAN 954_1 version with Logger consists of:

SVAN 954_1	Vibration Meter with SV 954_14 Logger
SV 3185D	Single axis general purpose accelerometer 100 mV/g
SC 27	Coil cable (TNC plug to TNC plug), providing connection of the SV 3185D accelerometer with the SVAN 954 instrument
SC 56	USB cable for communication with the PC
SvanPC+	Base module software for data download, visualisation and easy export to other applications
Certificate	Manufactory calibration certificate
Batteries	Four AA alkaline batteries

SVAN 954 analysis options :

SV 954_1	1/1 octave analysis option for the SVAN 954
SV 954_4	FFT analysis option for the SVAN 954
SV 954_8	Rotation measurement option without Laser Tachometer
SV 954_14	Time History Data Logger option for the SVAN 954

General vibrations measurements:

SA 27/3185D	Mounting magnet for accelerometer SV 3185D
SV RPM_PROB	Laser tachometer with SC 69 cable

Other accessories:

SA 18	Carrying bag for SVAN 954 and accessories (leather)
SA 47	Carrying bag (fabric material)
SA 15	Power supply from mains socket
SA 17A	External battery pack
SV 55	RS 232 interface option
SV 56	IrDA interface option
SC 35	Cable (Cinch plug to BNC plug) which provides easy access to I/O port, length 2meters